

# Heavy Duty Stamping Press HS-160H

*ING YU single-point high speed press has supplied to chain companies worldwide to make efficient chains for transferring energy through high tolerances and superior rigidity.*

## KEY FEATURES

### Alloy casting frame

3 sets of massive frame resist deflection and reduce vibration.

### 4 points crank supporting


2 bearings & 2 hydro-dynamic brass bushings are applied to get smaller clearance.

### Dynamic balancer

Dynamic balancer reserves weight of upper die to eliminate the inertia produced by reciprocation.

### Guiding system of slide

8 square guide gibs and linear bearings are applied to absorb the sideward thrust during stamping.





## **ING YU PRECISION INDUSTRIES CO., LTD.**

43-11 Sha-Tien Rd. Sha-Lu Dist., Taichung  
City 43354 TAIWAN

TEL: 886-4-26358569 FAX: 886-4-26353068

info@ingyu.com www.ingyu.com



Model	HS-160H			◆ Rigid Alloy Casting Frame
Capacity (ton)	160			◆ Dynamic Balance Device
Stroke (mm)	16	20	25	◆ Separated Clutch & Brake
Speed without loading (spm)	800	700	600	◆ Circulating Lubrication Device
Shut height (mm)	230 - 280			◆ Lubricant Refrigerant Cooler
Bolster area (mm)	1000 x 850			◆ Motorized Die Height Adjust
Slide area (mm)	1000 x 600			◆ Hydraulic Locking System
Slide adjustment (mm)	50			◆ Safety Guards
Main motor (hp)	30			◆ YASAKA Inverter